



VOC DATA SHEET

PROPERTIES OF THE MARINE COATING OR THINNER "AS SUPPLIED" BY THE MANUFACTURER

Manufacturer: AMERICAN SAFETY TECHNOLOGIES Product Identification: __S-31__

MACT Coating Category: General Use _____ or Specialty Coating _____

If coating is a Specialty Coating, please list the specific Category type(s) below (Refer to attached list of marine coating specialty categories).

N/A

Is this product a coating or thinner? COATING _____ THINNER __X__

If product is a coating or paint, please provide the information requested in Items A through J below:

If the product is thinner or reducer, please provide the information requested in Items D through J below:

Properties of the coating or thinner as supplied to the customer:

- A. Coating Density: (D_c) 868 g/L or 7.25 lbs/gal [] ASTM D1475-90 [X] Other
- B. Total Volatiles: (M_T) 100 Mass Percent [] ASTM D2369-93 [] Other
- C. Cure Volatiles Content: (C_{cv}) _____ g/L or 0 lbs/gal [] Calculated [] Other
- D. Organic Volatiles: (M_o) 100 Mass Percent [X] Calculated [] Other
- E. Water Content:
1. (M_w) 0 Mass Percent [] ASTM D3792-91 [] ASTM D4017-90 [] Other
2. (V_w) 0 Volume Percent [] Calculated [] Other
- F. Exempt Compounds Content: (C_{ex}) 0 g/L or 0 lbs/gal [] Calculated [] Other
- G. Non-volatiles (V_s) 0 Volume Percent [X] Calculated [] Other
- H. VOC Content (VOC)
1. _____ g/L or _____ lbs/gal solids (non-volatiles)
2. 868 g/L or 7.25 lbs/gal coatings (less water and exempt compounds)
- I. Thinner Density (D_{th}) 868 g/L or 7.25 lbs/gal [] ASTM _____ [] Other